

PRODUCT	Casaflex Cementitious		
MISSION	2-component cementitious waterproofing		
CHARACTERISTICS	Casaflex Cementitious is a 2-component flexible mortar screed waterproofing membrane. Due to its cement-based system, Casaflex cementitious is very good for adhesion with the concrete substrate. Easy to repair and high value product.		
APPEARENCE	Cement appearing		
CHARACTERISTICS	VALUE	TOLERANCE	U.M.
Mixed density	2.00	NA	Kh/lt
Tensile strength	1.4 MPA	NA	ASTM D412
Elongation	25 %	NA	ASTM D412
Initial Surface Absorption	0.02 ml	NA	(m ² /s)
Pot Life	30 minutes		
Colors available: Natural Cement Gray			
APPLICATION INSTRUCTIONS			
LAYING SURFACE	Mix 1 part A to 1 part B and mix with mixer. Install with soft brush or steel trowel, Rake. Apply 2 coat, crossed lines.		
CONSUMPTION	Consumption about 3kg/sqm, (about 1 to 1.5 lg/sqm/coat)		
TRAFFICABILITY	12 hours: Normal use on roof deck. 3-5 days: tiling allowed 5-7 days: water filling in tank allowed		
PACKAGING INSTRUCTIONS	COLOURS AVAILABLE	Part A: 20kg/bag Part B: 5 kg/drum	
STORAGE INSTRUCTIONS	STORAGE TEMPERATURE MIN -5° C – MAX 40° C	STABILITY IN THE ORIGINAL PACKAGE 12 months	
SAFETY STANDARDS	Please read the safety data sheet carefully before using this product.		